

X640 Compact Thermal Imager

EOTech X640 – Ruggedized Ultra Compact Thermal Imager with 640 x 480 resolution and advanced features!

FEATURES

- Simple one-button operation
- Greater scene detail with VGA 640 x 480 resolution
- Video port for simultaneous recording
- Covert operation with fully dimmable micro display
- Stows easily into pocket for quick extraction and agile operation in the field and on the run
- Customize camera features with provided user interface software



BENEFITS

- 30 Hz frame rate
- Detect human activity up to 1100 yards away
- 2x, 3x or 4x zoom
- White hot, black hot and 3 color modes
- Temperature measurement & cross hair enabled via supplied software CD
- Survives accidental drops and submersion
- Pocket-sized, weighing only 13 ounces (381 grams)
- Up to 5 hours runtime with two user-replaceable AA lithium batteries*
- Rugged design with integral rubber eye cup - 3-Year Warranty
- Tripod mount (1/4" - 20 thread)



CAMERA KIT INCLUDES

- USB Cable
- User Interface Software
- Lens Cloth
- Neck/Wrist Straps
- User Manual
- AA Batteries*



COVERT SURVEILLANCE
CRIME SCENE INVESTIGATION
SEARCH & RESCUE
MECHANICAL INSPECTION



ELECTRICAL INSPECTION
FUGITIVE PURSUIT
OUTDOOR RECREATION
FARMING/RANCHING



HUNTING GAME
RECOVERY
PRE-SEASON SCOUTING
ANTI-POACHING

*Compatible with AA alkaline batteries, but improved performance can be obtained with lithium-style batteries.

X640 TECHNICAL SPECIFICATIONS

FEATURES	X640	
GENERAL CHARACTERISTICS	MATERIAL & STRUCTURE	Amorphous Silicon Microbolometer
	PIXEL C	640 x 480 pixels
	SPECTRAL RESPONSE	7 to 14 μ m (filter bandwidth)
	THERMAL SENSITIVITY	\leq 50 mK
OPERATION		5 seconds (includes 2-second display of start-up logo)
	BRIGHTNESS/CONTRAST	Fully automatic
	RANGE TO DETECT HUMAN ACTIVITY	Up to 1100 yards
	OOM	2X to 10X e-zoom as default on power push button
OPTICS	INFRARED POLARITY	White hot, black hot, detection palettes and custom color modes
		24° x 18° (25mm) and 18° x 13.5° (35mm)
OPTICS		25 and 35 mm options
	MINIMUM FOCUS DISTANCE	3 ft. (1 m)
VIDEO		Simultaneous NTSC output available on rear outlet jack
	VIEWFINDER DISPLAY	Color LCD (640 x 480 pixels)
	VIEWFINDER DIMMING	Integral to power on/o
POWER		2 AA batteries (lithium recommended)*
	OPERATING TIME	6 hours with lithium at room temperature
	AUXILIARY POWER	12 VDC input on rear outlet jack
ENVIRONMENTAL CHARACTERISTICS	OPERATING TEMPERATURE	-4 °F to 140 °F (-20 °C to 60 °C)
	STORAGE TEMPERATURE	-4 °F to 176 °F (-20 °C to 80 °C)
	WATER & SHOCK RESISTANCE	Water-resistant to 3 ft. (1 m) submersion, buoyant. Shock-resistant (MIL-STD-810G, Method 516.6).
	EMC COMPLIANCE	FCC Part 15 & CE Mark
PHYSICAL DIMENSIONS		5 1/2" L x 4 1/2" W x 2" H (14 x 11.4 x 5.1 cm) (Both Models)
	WEIGHT	13 oz (369 g) for 25mm lens; 14 oz (397g) for 35mm lens, batteries installed
	EYE CUP	Integral to camera body
OPERATION		30 Hz - 24° Camera -5002330-1
		30 Hz - 18° Camera -5002331-1
CAMERA FEATURES	<ul style="list-style-type: none"> - White hot, black hot, detection palettes and custom color modes - On-screen battery level indicator - Left- or right-hand operation with rugged slip-resistant grip - 1/4 - 20 tripod mount 	<ul style="list-style-type: none"> - Tactile battery loading feature for stealth nighttime operation - External power input and video output jacks - Push-button control to activate feature set
STANDARD EQUIPMENT	<ul style="list-style-type: none"> - 2 AA lithium batteries - Neck strap & wrist strap - Lens cover 	<ul style="list-style-type: none"> - Lens cleaning cloth - USB cable - Interface software CD
OPTIONAL EQUIPMENT	<ul style="list-style-type: none"> - MOLLE-Compatible soft pouch - 5002070 - DVR cable 5002024 	<ul style="list-style-type: none"> - BNC video cable - 5002068 - A/C power adapter - 5002067



Please call for additional information.



ASPECT TECHNOLOGY & EQUIPMENT, INC

811 E Plano Pky #107 • Plano, TX 75074 • Phn 972-423-6008/Fax 972-423-7717 • email aspect@airmail.net • www.aspecttechnology.com



THERMAL-EYE™